

FOR HEATING
MEDIUM SPACES



FIREPLACES & STOVES

Neo 2.5 Insert



Transforms an energy-wasting fireplace into a cost-saving source of heat, without sacrificing the comfort and appeal of the home fire. Accommodating existing masonry fireplaces, the Neo 2.5 insert has Pacific Energy's trusted overbuilt steel construction, including a smooth opening cast iron door, boost air for easy lighting and a one-lever air control for simple operation and maximum burning efficiency. With all the features of the Neo 1.6 in a larger, higher-output format, the Neo 2.5 inserts deliver exceptional performance and durability.



Contemporary
Metallic Black



Contemporary
Stainless Steel

STANDARD FEATURES

- Reliable, durable non-catalytic technology
- Air wash system for super clean ceramic glass
- High-tech multi-port combustion air injection system
- Inside and outside combustion air capable
- Floating firebox for extended stove life
- Rich Metallic Black finish
- 304 Stainless Steel baffle, insulation cover, rails and flame shield
- Boost air for easy lighting
- Extended Burn Technology (EBT)
- Two 45 cfm temperature actuated variable speed blower/s
- Single-Lever Air Control
- Removable Cast-Iron Flue Collar

DESIGN OPTIONS

- Contemporary Surround in Metallic Black or Stainless Steel
- Oversize Surround

BTU Cord Wood	85,000 BTU
BTU EPA Test Fuel.	45,000 BTU
Efficiency (LHV)	TBD
Emissions.	TBD
Log Size	18 inches Max.